



INT-252 V2
Dual 15" Quasi 3-way Loudspeaker

INT-152 V2
15" 2-way Loudspeaker

INT-118S V2
Subwoofer

FEATURES

- 34 mm compression drivers
- Steel frame woofers
- PTC thermistor protected tweeter
- Black carpet finish
- 15 mm reinforced cabinet
- Speakon® and 1/4" inputs
- All metal handles with stamped CV logo

The Intense series from Cerwin-Vega! has established a well-deserved reputation for providing extraordinary and impactful sound at an affordable price. How do you enhance a leading product in its class? Improve the product components, sound quality AND lower the price! Introducing the new Intense! V2. Perfect for PA applications such as live sound, program playback, and DJ systems -- it can be installed in facilities, venues and clubs – yet it is fully portable for sound on the go.

So what's New?

Stronger drivers by beefing up the build quality with the addition of more steel.

Enhanced durability by upgrading the cabinet construction with internal bracing.

Better performance is achieved by increasing the size of the magnets on the compression drivers.

Improved dependability from a new positive temperature coefficient (PTC) thermistor that protects the tweeter. This component acts as a self-repairing fuse allowing the speaker to return to normal operation once the input fault is corrected.

Run longer. Run louder. Run with Cerwin-Vega!

Specifications & appearance subject to change.

USA: P 954.949.9600 • F 954.949.9590

EUROPE: P +32.2.645.05.00 • F +32.2.645.05.05

SPECIFICATIONS

	INT-152 V2	INT-252 V2	INT-118s V2
Frequency Response (1W /1M)	+/- 3 dB 64 Hz - 19.8 kHz -10 dB 46 Hz	+/- 3 dB 57 Hz - 19.8 kHz -10 dB 44 Hz	+/- 3 dB 49 Hz - 200 kHz -10 dB 33.5 Hz
Nominal Impedance (Ohms)	Full Range 8 Ohms	Full Range 4 Ohms	Full Range 8 Ohms
Axial Sensitivity (dB SPL, 1W / 1M)	Full Range 95 dB	Full Range 94 dB	Full Range 96 dB
Calculated Maximum Output (dB SPL, @ 1M)	Full Range 124 dB	Full Range 125 dB	Full Range 125.5 dB
Power Handling (Watts)	RMS 200 W Program 400 W Peak 800 W	RMS 350 W Program 700 W Peak 1400 W	RMS 225 W Program 450 W Peak 900 W
Nominal Coverage Angles / -6 dB points (Degrees)	Horizontal 90° Vertical 50°	Horizontal 90° Vertical 50°	Horizontal N/A Vertical N/A
Dimensions 152 & 252 (H x WF x WB x D) 118s (H x W x D)	30.75" x 18.5" x 10.375" x 19.25" 781mm x 470mm x 264mm x 489mm	46.5" x 18.5" x 10.375" x 19.25" 1181mm x 470mm x 264mm x 489mm	25.5" x 23.75" x 23" 648mm x 603mm x 584mm
Weight (Lbs / Kg)	57.70 Lbs. / 26.2 Kg	87.20 Lbs. (39.5 Kg)	88.85 Lbs. / 40.3 Kg

Specifications & appearance subject to change.

USA: P 954.949.9600 • F 954.949.9590

EUROPE: P +32.2.645.05.00 • F +32.2.645.05.05